ColorBlast Powercore gen4, RGBA OptiField

Date:	
Type:	
Firm Name:	
Project:	

High-performance OptiField exterior LED luminaire with RGBA light

ColorBlast Powercore gen4, RGBA OptiField boosts output and flexibility to meet the most demanding color lighting applications. Get high output, greater efficacy, precise color, remote monitoring, and more—all in a compact, reliable flood that's easy to customize and install. ColorBlast Powercore gen4, RGBA OptiField adds a separate amber LED which expands the available range of colors to include warmer tones such as rich gold, yellow, and orange shades. OptiField technology delivers extremely uniform (5:1) illuminance, providing smooth, even light and subtle shading—without hotspots or banding.

- ColorBlast Powercore gen4 integrates the latest LED innovations, custom optics, and a 100 to 277 VAC direct connection. The ColorBlast Powercore gen4 family still retains the rock-solid reliability and no-compromises quality that earned Blast its unequalled reputation.
- OptiField technology, features extremely uniform illumination (5:1 or better on a 5 m x 5 m (16.4 ft) wall with 1 m (3 ft) setback) providing smooth walls of light that appear perfect to the eye. And thanks to our breakthrough optics, you can place luminaires exceptionally close to illuminated surfaces.

Beam Angle	Wall Washing
Lumens*	1,227
Efficacy	25.8
LED Channels	Red/Green/Blue/Amber

19999	*****
A	5

Product page

Input Voltage	100 to 277 VAC, auto-ranging, 50/60 Hz via Data Enabler Pro	
Power Consumption	50 W	
Weight	3.9 kg (8.2 lb)	
Housing Material Die	-cast aluminium, white, black, or gray powder-coated finish	
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, RCM, EAC, UA	
Environment	Dry/Damp/Wet Location, IP66	
pplications Flood Lighting, Spot Lighting, Wall Wa		

Specification Sheets

PDF Download	Target Area Uniformity	ltem Number	12 NC
OptiField, RGBA, Black Housing	3.9:1	423-000019-01	912400136066
OptiField, RGBA, Gray Housing	3.9:1	423-000019-02	912400136067
OptiField, RGBA, White Housing	3.9:1	423-000019-00	912400136065

* Lumen output measurements comply with IES LM-79-08 testing procedures.



© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.