

Vaya Cove LP G2

High-efficiency, low profile, dimmable cove luminaire for crisp white lighting effects

Date: _____
Type: _____
Firm Name: _____
Project: _____

Vaya Cove LP G2 is a reliable cost-effective LED luminaire offering crisp white light for interior use. Designed for linear cove and accent lighting applications this luminaire offers a very low profile and integrated connectors to eliminate socket shadows. Vaya Cove LP offers on/off control or dimming via the use of any standard 0-10V or DALI dimming controller.

- Multiple lengths—Available in two standard nominal lengths, 305 mm (1 ft) and 1219 mm (4 ft). Custom options include an additional nominal 610 mm (2 ft) length.
- Multiple color temperatures—Luminaires are available in two standard color temperatures, 3000 K and 4000 K. Custom options include three additional color temperatures of 2200 K, 2700 K and 5000 K.
- Slim housing design—Low profile housing height of 21 mm (0.86 in), including mounting clips, allows for seamless design integration in tight spaces.



[Product page](#)

Beam Angle	110°
Lumens per foot*	254 to 279
Efficacy†	99.3 to 106
CRI @ 3000 K‡	82
CRI @ 4000 K‡	83
Color Temperature§	3000 K, 4000 K

Input Voltage	24 VDC
Weight	90 g (0.2 lb) 1 ft 360 g (0.8 lb) 4 ft
Housing Material	Extruded polycarbonate, white
Approbations	UL/cUL, FCC Class B, CE, CQC, CB, SELV
Environment	Damp Location, IP40
Applications	Cove Lighting

3000 K Specification Sheets

Custom products information available

PDF Download	Beam Angle	Lumens*	Efficacy†	CRI‡	Power	Weight	Item Number	12 NC
3000 K, 305 mm (1 ft), CE/CQC	110°	254	99.3	82	2.6 W	90 g (0.2 lb)	350-000017-00	912400135335
3000 K, 305 mm (1 ft), UL/CE	110°	274	103	82	2.7 W	90 g (0.2 lb)	350-000017-06	912400135341
3000 K, 1219 mm (4 ft), CE/CQC	110°	1,016	99.3	82	10.2 W	360 g (0.8 lb)	350-000017-02	912400135337
3000 K, 1219 mm (4 ft), UL/CE	110°	1,096	103	82	10.6 W	360 g (0.8 lb)	350-000017-08	912400135343

COLOR KINETICS
vaya series

4000 K Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy [†]	CRI [‡]	Power	Weight	Item Number	12 NC
4000 K, 305 mm (1 ft), CE/CQC	110°	255	100.6	83	2.5 W	90 g (0.2 lb)	350-000017-03	912400135338
4000 K, 305 mm (1 ft), UL/CE	110°	279	106	83	2.6 W	90 g (0.2 lb)	350-000017-09	912400135344
4000 K, 1219 mm (4 ft), CE/CQC	110°	1,020	100.6	83	10 W	360 g (0.8 lb)	350-000017-05	912400135340
4000 K, 1219 mm (4 ft), UL/CE	110°	1,116	106	83	10.5 W	360 g (0.8 lb)	350-000017-11	912400135346

* 305 mm (1 ft) lumen output measurements comply with IES LM-79-08 testing procedures. 610 mm (2 ft) and 1219 mm (4 ft) measurements are estimated based on the 305 mm (1 ft) measurements.

[†] Efficacy measurements are estimated based on the 305 mm (1 ft) measurements.

[‡] Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.

[§] CRI refers to CRI Ra value, CRI R9 refers to R9 value in accordance with IESNA LM-79 standards.

COLORKINETICS vayaseries

© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/vaya