

Vaya Flood MP G2 White

Mid-power exterior architectural floodlight with crisp white lighting

Date: _____
 Type: _____
 Firm Name: _____
 Project: _____

Vaya Flood MP (gen2) is a reliable and cost effective LED flood lighting solution for both exterior use that minimizes the initial investment, while providing exceptional flexibility to create eye-catching flood, wash and accent lighting effects. A wide choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.

- Powerful - Throwing light with 10lx up to 89 m / 1fc up to 292 ft high, this narrow beam luminaire is a powerful solution for any size of project.
- Compact - Unlike other flood lighting solutions, the Vaya Flood series are compact sized & light-weight luminaires, that combine an aluminium die-cast housing which is both anodized and powder coated to protect against corrosion, tempered glass, pressure equalizing air vents and IP66 outdoor rating, making the product robust against harsh outdoor environments.
- Simple - Direct line voltage input eliminates the need for remote power supply unit, minimizing the system components and risk points, allowing for an easy and fast installation.



[Product page](#)

Beam Angles	10°, 20°, 40°
Lumens	5,180 to 6,312
Color Temperature	3000 K, 4000 K
Applications	Flood Lighting, Spot Lighting, Wall Washing
Environment	Dry/Damp/Wet Location, IP66

Input Voltage	120 to 277 VAC, 50/60 Hz and 220 to 240 VAC, 50/60 Hz
Power Consumption	68 W
Weight	5.72 kg (12.61 lb)
Housing Material	Die-cast aluminium, dark grey powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, RCM, BIS

Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	CRI†	Item Number	12 NC
3000 K, 10°, CE/CQC	10°	5,773	84.6	80	350-000016-00	912400134020
3000 K, 20°, CE/CQC	20°	5,660	83.5	80	350-000016-01	912400134021
3000 K, 40°, CE/CQC	40°	5,180	76.3	80	350-000016-02	912400134022
3000 K, 10°, UL	10°	5,773	84.6	80	350-000016-16	912400134026
3000 K, 20°, UL	20°	5,660	83.5	80	350-000016-17	912400134027
3000 K, 40°, UL	40°	5,180	76.3	80	350-000016-18	912400134028
3000 K, 10°, BIS	10°	5,773	84.6	80	350-000016-68	912400137264
3000 K, 20°, BIS	20°	5,660	83.5	80	350-000016-69	912400137265
3000 K, 40°, BIS	40°	5,180	76.3	80	350-000016-70	912400137266
4000 K, 10°, CE/CQC	10°	6,312	93.3	82	350-000016-08	912400134023
4000 K, 20°, CE/CQC	20°	6,150	90.8	82	350-000016-09	912400134024
4000 K, 40°, CE/CQC	40°	5,634	83.3	82	350-000016-10	912400134025
4000 K, 10°, UL	10°	6,312	93.3	82	350-000016-24	912400134029
4000 K, 20°, UL	20°	6,150	90.8	82	350-000016-25	912400134030
4000 K, 40°, UL	40°	5,634	83.3	82	350-000016-26	912400134031
4000 K, 10°, BIS	10°	6,312	93.3	82	350-000016-71	912400137267
4000 K, 20°, BIS	20°	6,150	90.8	82	350-000016-72	912400137268
4000 K, 40°, BIS	40°	5,634	83.3	82	350-000016-73	912400137269

© 2021 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

www.colorkinetics.com/global/products/vaya/flood-mp-g2-white

21 October 2021

COLOR KINETICS vaya series