

Vaya Linear LP RGB

Ultra compact exterior-rated line-voltage linear LED grazing luminaire for dynamic color-changing lighting effects

Date: _____
Type: _____
Firm Name: _____
Project: _____

Vaya Linear LP is a super slim outdoor linear luminaire for low-level grazing applications, with wide 120° beam or elliptical 28° x 84° optics. Its slim form factor is ideal for space-restricted applications with limited setback or allowable install height. The robust Vaya Linear LP offers a variety of color and white CCT options with either static on/off- or dynamic control options via standard DMX-512. The discreet design with integrated power supply and waterproof connectors makes wiring simple, fast and reliable.

- Compact - With its miniature size and custom-designed optics, the Linear LP is ideal for small spaces and close setback distances.
- Simple - Directly processes 100 to 240 VAC input, all in one slim housing, eliminating the need for bulky external low voltage power supplies and related cabling limitations, allowing for greater installation flexibility and a lean installation. Optional On-Off or DMX-512 control allows for dimming and dynamic control with industry standard protocols, allowing for easy setup and 3rd party system integration.

[Product page](#)

Beam Angle	28° x 84°, 120°	Input Voltage	100 to 240 VAC, 50/60 Hz
Lumens per foot*	144 to 152	Weight	1 kg (2.2 lb) for 2 ft 2 kg (4.4 lb) for 4 ft
Efficacy for 28°x84°	22.8	Housing Material	Extruded aluminium, dark grey anodized finish
Efficacy for 120°	24.1	Approbations	UL/cUL, FCC Class A, CE, PSE, RCM
LED Channels	Red/Green/Blue	Environment	Dry/Damp/Wet Location, IP66
		Applications	Wall Grazing

Specification Sheets

PDF Download	Beam Angle	Lumens*	Power	Weight	Item Number	12 NC
RGB, 120°, 0.6 m (2 ft), CE	120°	305	14 W	1.0 kg (2.2 lb)	316-000010-00	910503704421
RGB, 120°, 0.6 m (2 ft), UL	120°	305	14 W	1.0 kg (2.2 lb)	316-000010-04	910503704425
RGB, 120°, 1.2 m (4 ft), CE	120°	611	28 W	2.0 kg (4.4 lb)	316-000010-02	910503704423
RGB, 120°, 1.2 m (4 ft), UL	120°	611	28 W	2.0 kg (4.4 lb)	316-000010-06	910503704427

COLORKINETICS
vaya series

Specification Sheets

PDF Download	Beam Angle	Lumens*	Power	Weight	Item Number	12 NC
RGB, 28° x 84°, 0.6 m (2 ft), CE	28° x 84°	288	14 W	1.0 kg (2.2 lb)	316-000010-01	910503704422
RGB, 28° x 84°, 0.6 m (2 ft), UL	28° x 84°	288	14 W	1.0 kg (2.2 lb)	316-000010-05	910503704426
RGB, 28° x 84°, 1.2 m (4 ft), CE	28° x 84°	576	28 W	2.0 kg (4.4 lb)	316-000010-03	910503704424
RGB, 28° x 84°, 1.2 m (4 ft), UL	28° x 84°	576	28 W	2.0 kg (4.4 lb)	316-000010-07	910503704428

* Lumen output measurements comply with IES LM-79-08 testing procedures.

COLORKINETICS vayaseries

© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/vaya