

Vaya Linear MP Landscape

Powerful exterior linear sign lighter with single temperature white light

Date: _____
 Type: _____
 Firm Name: _____
 Project: _____

Vaya Linear MP Landscape is an exterior-rated LED sign lighter solution that minimizes initial investment. Adjustable landscape mounts allow for seamless NPT gland mounting, while the discreet design with integrated power supply ensure simple and reliable wiring.

- **Powerful** - Throwing light with 10lx up to 22 m / 1fc up to 72 ft (wide beam), the Linear MP Landscape is ideal for lighting up signage and landscape sculptures.
- **Simple** - Directly processes 100 to 240 VAC input, all in one slim housing, eliminating the need for bulky external low voltage power supplies and related cabling limitations, allowing for greater installation flexibility and a lean installation.
ESTA DMX-512 control allows for dimming and dynamic control with industry standard protocols, allowing for easy setup and 3rd party system integration.
- **Robust** - An anodized aluminium housing, tempered glass, pressure equalizing air vents and IP66 outdoor rating protect this product against harsh outdoor environments.



[Product page](#)

Beam Angle	10° x 50°, 50°
Lumens per foot*	848 to 874
Efficacy @ 3000 K	57.9
Efficacy @ 4000 K	61.1
CRI @ 3000 K†	78
CRI @ 4000 K†	83
Color Temperature [§]	3000 K, 4000 K

Input Voltage	100 to 277 VAC, 50/60 Hz
Weight	1.3 kg (2.9 lb) for 1 ft 3.6 kg (7.9 lb) for 4 ft
Housing Material	Extruded aluminium, dark grey anodized finish
Approbations	UL/cUL, FCC Class A
Environment	Dry/Damp/Wet Location, IP66
Applications	Wall Grazing

3000 K Specification Sheets

Custom products information available

PDF Download	Beam Angle	Lumens*	Efficacy	CRI†	Power	Weight	Item Number	12 NC
3000 K, 50°, 0.3 m (1 ft), UL, Landscape Mount	50°	848	57.9	78	18 W	1.3 kg (2.9 lb)	350-000011-48	912400130165
3000 K, 50°, 1.2 m (4 ft), UL, Landscape Mount	50°	3,392	57.9	78	60 W	3.6 kg (7.9 lb)	350-000011-49	912400130166

4000 K Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	CRI [†]	Power	Weight	Item Number	12 NC
4000 K, 50°, 0.3 m (1 ft), UL, Landscape Mount	50°	874	61.1	83	18 W	1.3 kg (2.9 lb)	350-000011-50	912400130167
4000 K, 50°, 1.2 m (4 ft), UL, Landscape Mount	50°	3,496	61.1	83	60 W	3.6 kg (7.9 lb)	350-000011-51	912400130168

* Lumen output measurements comply with IES LM-79-08 testing procedures.

[‡] Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.

[†] CRI refers to CRI Ra value, CRI R9 refers to R9 value in accordance with IESNA LM-79 standards.

COLORKINETICS vayaseries

© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/vaya