

Vaya Linear MP White

Powerful exterior line-voltage linear grazing luminaire with crisp white lighting

Date: _____
Type: _____
Firm Name: _____
Project: _____

Vaya Linear MP is a reliable and cost-effective LED wall grazing luminaire for both interior and exterior use that minimizes initial investment, while offering exceptional flexibility to create eye-catching wall washing and wall grazing effects. A wide range of color and CCT options, static on/off control, adjustable mounting brackets, wide or elliptical beam angles offer a comprehensive toolbox for your facade lighting needs. The discreet design with integrated power supply makes wiring simple, fast, and reliable.

- Powerful - Throwing light with 10lx up to 39 m / 1fc up to 128 ft (elliptical beam), the Linear MP is ideal for grazing of mid-sized walls and facades.
- Simple - Directly processes 100 to 277 VAC input, all in one slim housing, eliminating the need for bulky external low voltage power supplies and related cabling limitations, allowing for greater installation flexibility and a lean installation. Standard On-Off or custom DMX-512 control allows for dimming and dynamic control with industry standard protocols, allowing for easy setup and 3rd party system integration.



[Product page](#)

Beam Angle	10° x 50°, 50°
Lumens per foot*	792 to 874
Efficacy	54.3 to 61.1
CRI @ 3000 K†	78
CRI @ 4000 K†	83
Color Temperature [§]	3000 K, 4000 K

Input Voltage	100 to 277 VAC, 50/60 Hz
Weight	1.3 kg (2.9 lb) for 1 ft 3.6 kg (7.9 lb) for 4 ft
Housing Material	Extruded aluminium, dark grey anodized finish
Approbations	UL/cUL, FCC Class A, CE, PSE, RCM
Environment	Dry/Damp/Wet Location, IP66
Applications	Wall Grazing

3000 K Specification Sheets

Custom products information available

PDF Download	Beam Angle	Lumens*	Efficacy	CRI†	Power	Weight	Item Number	12 NC
3000 K, 50°, 0.3 m (1 ft), CE	50°	848	57.9	78	18 W	1.3 kg (2.9 lb)	350-000011-00	912400130117
3000 K, 50°, 0.3 m (1 ft), UL	50°	848	57.9	78	18 W	1.3 kg (2.9 lb)	350-000011-08	912400130125
3000 K, 50°, 1.2 m (4 ft), CE	50°	3,392	57.9	78	60 W	3.6 kg (7.9 lb)	350-000011-02	912400130119
3000 K, 50°, 1.2 m (4 ft), UL	50°	3,392	57.9	78	60 W	3.6 kg (7.9 lb)	350-000011-10	912400130127

COLOR KINETICS
vaya series

3000 K Specification Sheets (cont.)

PDF Download	Beam Angle	Lumens*	Efficacy	CRI [‡]	Power	Weight	Item Number	I2 NC
3000 K, 10° x 50°, 0.3 m (1 ft), CE	10° x 50°	792	54.3	78	18 W	1.3 kg (2.9 lb)	350-000011-01	912400130118
3000 K, 10° x 50°, 0.3 m (1 ft), UL	10° x 50°	792	54.3	78	18 W	1.3 kg (2.9 lb)	350-000011-09	912400130126
3000 K, 10° x 50°, 1.2 m (4 ft), CE	10° x 50°	3,169	54.3	78	60 W	3.6 kg (7.9 lb)	350-000011-03	912400130120
3000 K, 10° x 50°, 1.2 m (4 ft), UL	10° x 50°	3,169	54.3	78	60 W	3.6 kg (7.9 lb)	350-000011-11	912400130128

4000 K Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	CRI [‡]	Power	Weight	Item Number	I2 NC
4000 K, 50°, 0.3 m (1 ft), CE	50°	874	61.1	83	18 W	1.3 kg (2.9 lb)	350-000011-04	912400130121
4000 K, 50°, 0.3 m (1 ft), UL	50°	874	61.1	83	18 W	1.3 kg (2.9 lb)	350-000011-12	912400130129
4000 K, 50°, 1.2 m (4 ft), CE	50°	3,496	61.1	83	60 W	3.6 kg (7.9 lb)	350-000011-06	912400130123
4000 K, 50°, 1.2 m (4 ft), UL	50°	3,496	61.1	83	60 W	3.6 kg (7.9 lb)	350-000011-14	912400130131
4000 K, 10° x 50°, 0.3 m (1 ft), CE	10° x 50°	844	59	83	18 W	1.3 kg (2.9 lb)	350-000011-05	912400130122
4000 K, 10° x 50°, 0.3 m (1 ft), UL	10° x 50°	844	59	83	18 W	1.3 kg (2.9 lb)	350-000011-13	912400130130
4000 K, 10° x 50°, 1.2 m (4 ft), CE	10° x 50°	3,375	59	83	60 W	3.6 kg (7.9 lb)	350-000011-07	912400130124
4000 K, 10° x 50°, 1.2 m (4 ft), UL	10° x 50°	3,375	59	83	60 W	3.6 kg (7.9 lb)	350-000011-15	912400130132

* Lumen output measurements comply with IES LM-79-08 testing procedures.

[‡] Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.

[‡] CRI refers to CRI Ra value, CRI R9 refers to R9 value in accordance with IESNA LM-79 standards.

COLORKINETICS **vaya**series

© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/vaya