



NOTE:

- MAXIMUM CAT5 RUN BETWEEN DEVICES IS 330 FEET (100m). CONTACT COLOR KINETICS TECHNICAL SUPPORT FOR INSTALLATIONS REQUIRING CUSTOM NETWORK CONFIGURATIONS.
- THE LEADER CABLE IS CONNECTORIZED TO ENSURE FAULTLESS WIRING. DO NOT REMOVE OR REPLACE THE FACTORY INSTALLED CONNECTORS.
- DO NOT SHORTEN, LENGTHEN, OR MODIFY THE LEADER CABLE. CUTTING THE LEADER CABLE MAY DAMAGE THE DATA DRIVE CIRCUITRY.

ADDRESSING AND CONTROL:

- LIGHTS ARE AUTOMATICALLY DISCOVERED AND ADDRESSED USING LIGHT SYSTEM COMPOSER SOFTWARE PACKAGE. REFER TO USER GUIDE FOR FURTHER INSTRUCTIONS ON ADDRESSING AND CONTROL
- WHEN CREATING SHOWS WITH LIGHT SYSTEM COMPOSER SOFTWARE USE RGB EFFECTS WITH EITHER WHITE (ON) OR BLACK (OFF). CONTACT TECHNICAL SUPPORT FOR FUTURE ASSISTANCE WITH PROGRAMMING.



COPYRIGHT © 2007 PHILIPS SOLID-STATE LIGHTING SOLUTIONS. ALL RIGHTS RESERVED. CHROMACORE, CHROMALUX, OR THE COLOR KINETICS LOGO, COLOR KINETICS, THE COLOR KINETICS LOGO, COLOR KINETICS THE LEADER IN INTELLIGENT LIGHT, COLORBLAST, COLORBLAZE, COLORBLISS, COLORCAST, COLORPLAY, COLORSCAPE, BRAND, DIRECT LIGHT, ESSENTIALWHITE, eW, KOLOR, KOLOR CODE, INTELLIWHITE, IN PLAYERS LIGHT, INHOUST, LUMES, OPTIMA, POWERCORE, QUICKPLAY, SAUCE, THE SAUCE LOGO, AND SMARTLACE ARE EITHER REGISTERED TRADEMARKS OR TRADEMARKS OF PHILIPS SOLID-STATE LIGHTING SOLUTIONS IN THE UNITED STATES AND/OR OTHER COUNTRIES. ALL OTHER BRAND OR PRODUCT NAMES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

DATA TERMINATOR NOTE REQUIRED WITH ETHERNET SYSTEMS

DATA CABLES (UTP)
ACCEPTABLE CABLE TYPES:
CAT-5/CAT-5e/CAT-6
STRAIGHT-THROUGH (T568B)

TITLE: SYSTEM WIRING DIAGRAM (TYP)
PRODUCTS: eW FLEX SLX/sPDS-480ca 24V/LIGHT SYSTEM MANAGER/ ETHERNET CONTROLLER KEYPAD/PS-60

DATE: 8-1-2008
DWG. BY: BHG
SCALE: NTS
REV:
PAGE: 1 OF 1