



**ADDRESSING AND CONTROL:**  
 -LIGHTS ARE AUTOMATICALLY DISCOVERED AND ADDRESSED USING LIGHT SYSTEM COMPOSER SOFTWARE PACKAGE. REFER TO USER GUIDE FOR FURTHER INSTRUCTIONS ON ADDRESSING AND CONTROL  
 -WHEN CREATING SHOWS WITH LIGHT SYSTEM COMPOSER SOFTWARE USE RGB EFFECTS WITH EITHER WHITE (ON) OR BLACK (OFF). CONTACT TECHNICAL SUPPORT FOR FUTURE ASSISTANCE WITH PROGRAMMING.

**NOTE:**  
 - MAXIMUM CAT5 RUN BETWEEN DEVICES IS 330 FEET (100m). CONTACT COLOR KINETICS TECHNICAL SUPPORT FOR INSTALLATIONS REQUIRING CUSTOM NETWORK CONFIGURATIONS.  
 - THE LEADER CABLE IS CONNECTORIZED TO ENSURE FAULTLESS WIRING. DO NOT REMOVE OR REPLACE THE FACTORY INSTALLED CONNECTORS.  
 - DO NOT SHORTEN, LENGTHEN, OR MODIFY THE LEADER CABLE. CUTTING THE LEADER CABLE MAY DAMAGE THE DATA DRIVE CIRCUITRY.



COPYRIGHT © 2007 PHILIPS SOLID-STATE LIGHTING SOLUTIONS. ALL RIGHTS RESERVED. CHROMACORE, CHROMASC, CC, THE CC LOGO, COLOR KINETICS, THE COLOR KINETICS LOGO, COLOR KINETICS THE LEADER IN FULL BENT LIGHT, COLORBLAST, COLORBLAZE, COLORBURST, COLORCAST, COLORPLAY, COLORSCAPE, COLORSHIFT, BRIGHT, LIGHTS, LIGHTS IN THE DARK, KINOCORE, INTELLIWAYS, IN-PLAYER LIGHT WITHOUT LIMITS, OPTIBIN, POWERSCAPE, QUICKPLAY, SCAUCE, THE SAUCE LOGO, AND SMARTFACE ARE EITHER REGISTERED TRADEMARKS OR TRADEMARKS OF PHILIPS SOLID-STATE LIGHTING SOLUTIONS IN THE UNITED STATES AND/OR OTHER COUNTRIES. ALL OTHER BRAND OR PRODUCT NAMES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

DATA TERMINATOR  
NOTE REQUIRED WITH  
ETHERNET SYSTEMS

DATA CALBES (TUP)  
ACCEPTABLE CABLE TYPES:  
CAT-5/CAT-5e/CAT-6  
STRAIGHT-THROUGH (T568B)

TITLE: SYSTEM WIRING DIAGRAM (TYP)  
PRODUCTS: eW FLEX SLX/sPDS-60ca 24V DMX/ETHERNET/  
LIGHT SYSTEM MANAGER

DATE:	8-1-2008
DWG. BY:	BHG
SCALE:	NTS
REV:	
PAGE:	1 OF 1