



NOTE: MINIMUM CABLE RUN BETWEEN DEVICES IS 300 FEET (91.44M) CONTACT COLOR KINETICS TECHNICAL SUPPORT FOR INSTALLATIONS REQUIRING CUSTOM NETWORK CONFIGURATIONS.

- THE LEADER CABLE IS CONNECTORIZED TO ENSURE FAIL TOLERANCE

- DO NOT SHORTEN, LENGTHEN, OR MODIFY THE LEADER CABLE. CUTTING THE LEADER CABLE MAY DAMAGE THE DATA DRIVE CIRCUITRY.

	COLOR KINETICS INCORPORATED 10 MILK STREET SUITE 1100 BOSTON, MA 02108 TEL. 1.888.FULL RGB	DATA TERMINATION NETWORKS ETHERNET SYSTEMS	ACCEPTABLE CABLE TYPES CAT5e/CAT6/CAT6A STRAIGHT THROUGH (S/ST)	TITLE SYSTEM WIRING DIAGRAM (TYP)	DATE 12/26/2010
	COLOR KINETICS INCORPORATED 10 MILK STREET SUITE 1100 BOSTON, MA 02108 TEL. 1.888.FULL RGB	DATA TERMINATION NETWORKS ETHERNET SYSTEMS	ACCEPTABLE CABLE TYPES CAT5e/CAT6/CAT6A STRAIGHT THROUGH (S/ST)	PRODUCT COLOR FLEX SIX/RGB-12V/LIGHT SYSTEM MANAGER/ETHERNET CONTROLLER KEYPAD/PS-60	DRAWN BY BRG
COLOR KINETICS INCORPORATED 10 MILK STREET SUITE 1100 BOSTON, MA 02108 TEL. 1.888.FULL RGB	DATA TERMINATION NETWORKS ETHERNET SYSTEMS	ACCEPTABLE CABLE TYPES CAT5e/CAT6/CAT6A STRAIGHT THROUGH (S/ST)	MANAGER/ETHERNET CONTROLLER KEYPAD/PS-60	PAGE 1 OF 1	WWW.COLORKINETICS.COM