



OUT TO ADDITIONAL PWS UNITS OR OUT TO FAN SYSTEMS FOR TOTAL TO 8 LEVELS IN TOTAL

NOTE:  
 - MAXIMUM CAT5 RUN BETWEEN DEVICES IS 330 FEET (100M), CONTACT COLOR KINETICS TECHNICAL SUPPORT FOR INSTALLATIONS REQUIRING CUSTOM NETWORK CONFIGURATIONS UNEXPECTED TO ENSURE FAUL TLESS  
 - LEADER CANNOT BE REVERSE ENGINEERED TO ENSURE FAUL TLESS  
 - VISUALS DO NOT REMOVE OR REPLACE THE FACTORY INSTALLED CONNECTORS - DO NOT SHORTEN, LENGTHEN, OR MODIFY THE LEADER CABLE. CUTTING THE LEADER CABLE MAY DAMAGE THE DATA DRIVE CIRCUITRY.



Color Kinetics is a registered trademark of Color Kinetics, Inc. All other trademarks are the property of their respective owners. © 2006 Color Kinetics, Inc. All rights reserved. Color Kinetics, Inc. is not responsible for any damage to property or equipment caused by the use of this product. Color Kinetics, Inc. is not responsible for any damage to property or equipment caused by the use of this product. Color Kinetics, Inc. is not responsible for any damage to property or equipment caused by the use of this product.

DATA TERMINATOR NOTE REQUIRED WITH ETHERNET SYSTEMS

DATA CABLES (UTP) ACCEPTABLE CABLE TYPES: STRAIGHT THROUGH (568B)

TITLE: SYSTEM WIRING DIAGRAM (TYP)

PRODUCTS: ICOLOR FLEX SLX/SP12S4800CA 12V/LIGHT SYSTEM MANAGER

DATE: 12-26-2006  
 DWG. BY: BHG  
 SCALE: NTS  
 REV: BHG 8-25-2007  
 PAGE: 1 OF 1