



- NOTE:**
- MAXIMUM CAT5 RUN BETWEEN DEVICES IS 330 FEET (100m). CONTACT COLOR KINETICS TECHNICAL SUPPORT FOR INSTALLATIONS REQUIRING CUSTOM NETWORK CONFIGURATIONS.
 - MAXIMUM NUMBER OF LIGHTS PER PDS-60ca: 30 (ALL ON ONE OUTPUT OR DIVIDED BETWEEN THE TWO OUTPUTS).
 - DO NOT SHORTEN OR LENGTHEN LEADER CABLE. CUTTING THE LEADER CABLE WILL DAMAGE THE DATA DRIVE CIRCUITRY.
 - WHEN USING 1-FT JUMPER CABLES CONTACT APPLICATION ENGINEERING FOR RUN LIMITATIONS.

PHILIPS

COPYRIGHT © 2007 PHILIPS SOLID-STATE LIGHTING SOLUTIONS. ALL RIGHTS RESERVED. CHROMACORE, CHROMASC, CK, THE CK LOGO, COLOR KINETICS, THE COLOR KINETICS LOGO, COLOR KINETICS THE LEADER INTELLIGENT LIGHT, COLORBLAST, COLORGLAZE, COLORBURST, COLORCAST, COLORPLAY, COLORSCAPE, CRYMAG, DIRECT LIGHT, ESDINTELLIGENT, iV, ICOLOR, ICOLOR COVE, INTELLIWHITE, iV, iPLAYER, LIGHT WITHOUT LIMITS, OPTIBIN, iPE, POWERCORE, QUICKPLAY, SANGU, THE SANGU LOGO, AND SHARPLINE ARE EITHER REGISTERED TRADEMARKS OR TRADEMARKS OF PHILIPS SOLID-STATE LIGHTING SOLUTIONS IN THE UNITED STATES AND/OR OTHER COUNTRIES. ALL OTHER BRAND OR PRODUCT NAMES ARE TRADEMARKS OR REGISTERED TRADEMARKS OF THEIR RESPECTIVE OWNERS.

DATA TERMINATOR
NOTE REQUIRED WITH
ETHERNET SYSTEMS

DATA CABLES (UTP)
ACCEPTABLE CABLE TYPES:
CAT-5/CAT-5e/CAT-6
STRAIGHT-THROUGH (T568B)

TITLE: SYSTEM WIRING DIAGRAM (TYP)
PRODUCTS: iCOLOR COVE EC/PDS-60ca 24V/LIGHT SYSTEM
MANAGER/ETHERNET CONTROLLER KEYPAD

DATE: 3-12-2008
DWG. BY: BHG
SCALE: NTS
REV: BHG: 6-6-2008
PAGE: 1 OF 1