


- NOTES:**
- EACH PDS-150e WILL SUPPORT TWO (2) RUNS OF iCOLOR FRESKO.
 - EACH RUN CAN CONTAIN A MAX. OF 12 LINEAR FT. OF iCOLOR FRESKO FIXTURES, FOR A TOTAL OF 24 L.F. PER PDS-150e.
 - USE 3 CONDUCTOR, 14-16 AWG LEAD CABLES (SUPPLIED BY OTHERS) FROM PDS-150e TO FIRST JUNCTION BOX.
 - MAX. RUN LENGTH, OF EACH LEAD CABLE INCLUDING FIXTURE = 50 FT.

CAUTION: CONNECT ONLY 1 FIXTURE RUN (12 L.F.) TO A FUSE GROUP

CONTINUE DMX OUT/IN SEQUENCE TO INCLUDE ALL PWR/DATA SUPPLIES, THEN TERMINATE THE LAST UNIT (SEE BELOW)


DATA TERMINATOR



PLACE IN DMX LOOP OUT PORT OF POWER/DATA SUPPLY WHEN REQUIRED (SEE NOTES)

NOTE:

- USE DMX OUT REPEATER (INSTEAD OF LOOP OUT) ON EVERY 32nd PDS UNIT IN A CHAIN, OR WHEN A DATA CABLE RUN BETWEEN UNITS EXCEEDS 400'. WHEN USING THE DMX OUT REPEATER, PLACE A DATA TERMINATOR IN THE DMX LOOP OUT PORT OF THAT PDS UNIT (SEE ABOVE).



COLOR KINETICS INCORPORATED
 10 MILK STREET, SUITE 1100
 BOSTON, MA 02108
 888 FULL RGB
 617 423 9999
 WWW.COLORKINETICS.COM

FULL SPECTRUM DIGITAL LIGHTING

TITLE:
 SYSTEM WIRING DIAGRAM (TYP)

PRODUCTS:
 iCOLOR FRESKO/PDS-150e/iPLAYER 2/
 CONTROLLER KEYPAD

DATE:

DWG. BY: TC

SCALE: NTS

REV:

PAGE: 1 OF 1