



Date: _____
 Type: _____
 Firm Name: _____
 Project: _____

ColorBlast 6

The original compact exterior LED wash luminaire with intelligent color light

High-performance ColorBlast 6 LED luminaires generate rich, saturated colors and color-changing effects for a range of wall-washing and floodlighting applications. Designed with the needs of lighting designers and architects in mind, ColorBlast 6 can be used in both indoor and outdoor installations. High-intensity LEDs produce superior light output in a compact, low-profile housing. ColorBlast 6 also offers full pan and tilt rotation, flexible mounting options, two beam angles, and superior control through Color Kinetics or third-party controllers.

- Two beam patterns—A frosted glass lens (21° beam angle) produces a soft-edge beam, while a clear glass lens (10° beam angle) affords extended light projection.
- Outdoor rated—Fully sealed for maximum luminaire life and IP66-rated for outdoor applications, ColorBlast 6 luminaires meet or exceed specifications for use in wet locations. Rugged, die-cast aluminium housing is available in white or black powder-coated finish.
- Flexible mounting options—The versatile luminaire canopy base can be mounted to a junction box or directly to a wall, ceiling, or floor. A liquid-tight cable fitting seals the canopy opening for use in damp or wet environments.



[Product page](#)

Beam Angle	10°, 21°
Lumens*	534 to 584
Efficacy	13 to 14.2
LED Channels	Red/Green/Blue
Input Voltage	24 VDC via PDS-150e or PDS-60
Power Consumption	25 W
Weight	2.95 kg (6.5 lb)
Housing Material	Die-cast aluminium, powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, C-Tick, SAA
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC
10° Clear Lens, Black Housing	10°	584	14.2	116-000026-03	910503700596
10° Clear Lens, White Housing	10°	584	14.2	116-000026-02	910503700595
21° Frosted Lens, Black Housing	21°	534	13	116-000026-01	910503700594
21° Frosted Lens, White Housing	21°	534	13	116-000026-00	910503700593

* Lumen output measurements comply with IES LM-79-08 testing procedures.

© 2018 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

10/11/2018

Color Kinetics
www.colorkinetics.com/ls/rgb/colorblast6/