

ColorBurst IntelliHue Powercore, Optifield

Architectural and landscape spotlight with intelligent white and color light

Date: _____
 Type: _____
 Firm Name: _____
 Project: _____

ColorBurst IntelliHue Powercore brings the precise control of color and high-quality tunable white light in the same luminaire for outdoor wall washing and spot lighting applications. The IntelliHue technology delivers 80+ CRI (2700 K to 4000 K) and the ability to tint any CCT between 2000 K and 10000 K above and below the black-body curve. OptiField technology delivers extremely uniform illuminance, providing smooth, even light and subtle shading with reduced setbacks—without hotspots or banding.

- OptiField technology features extremely uniform illumination (6.3:1 or better on a 6 x 4.3 m (14 x 19.7 ft) wall with 1 m (3 ft) setback) providing smooth walls of light that appear perfect to the eye. And thanks to our breakthrough optics, you can place luminaires exceptionally close to illuminated surfaces.
- Expands customization with a wide range of options. Four housing color choices (black, gray, white, and bronze)—plus the option to add a half glare shield—create new aesthetic possibilities for designers and architects.



[Product page](#)

Lumens All Channels Full On*	827
Efficacy (lm/W) All Channels Full On	28.5
CRI at 2700 K [§]	88
LED Channels	Red/Green/Blue/Mint White

Input Voltage	100 to 277 VAC, auto-ranging, 50/60 Hz
Power Consumption	33 W
Weight	3.5 kg (7.7 lb) Landscape 5.5 kg (12.1 lb) Architectural
Housing Material	Die-cast aluminium, powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, RCM
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

Specification Sheets

PDF Download	Target Area Uniformity	Item Number	12 NC
OptiField, Black Housing, Landscape	5.2:1	423-000003-33	912400136620
OptiField, Bronze Housing, Landscape	5.2:1	423-000003-37	912400136624
OptiField, Gray Housing, Landscape	5.2:1	423-000003-31	912400136618
OptiField, White Housing, Landscape	5.2:1	423-000003-35	912400136622

Specification Sheets (cont.)

PDF Download	Target Area Uniformity	Item Number	12 NC
OptiField, Black Housing, Architectural	5.2:1	423-000003-34	912400136621
OptiField, Bronze Housing, Architectural	5.2:1	423-000003-38	912400136625
OptiField, Gray Housing, Architectural	5.2:1	423-000003-32	912400136619
OptiField, White Housing, Architectural	5.2:1	423-000003-36	912400136623

* Lumen output measurements comply with IES LM-79-08 testing procedures.

§ CRI refers to CRI Ra value, CRI R9 refers to R9 value in accordance with IESNA LM-79 standards.



© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/Is/IntelliHue/ColorBurst-Powercore-Optifield/