

Vaya Flood MP G2 RGB

Mid-power exterior architectural floodlight with dynamic color-changing lighting effects

Date: _____
 Type: _____
 Firm Name: _____
 Project: _____

Vaya Flood MP (gen2) is a reliable and cost effective LED flood lighting solution for both exterior use that minimizes the initial investment, while providing exceptional flexibility to create eye-catching flood, wash and accent lighting effects. A wide choice of beam angles and color options let you bring a property to life with either static or dynamically changing colors. Extended light throw and high efficacy set this compact & robust luminaire apart. Its integrated power and adjustable tilt angle make this product versatile and easy to use.

- **Powerful** - Throwing light with 10lx up to 78 m / 1fc up to 254 ft high, this narrow beam luminaire is a powerful solution for any size of project.
- **Compact** - Unlike other flood lighting solutions, the Vaya Flood series are compact sized & light-weight luminaires, that combine an aluminium die-cast housing which is both anodized and powder coated to protect against corrosion, tempered glass, pressure equalizing air vents and IP66 outdoor rating, making the product robust against harsh outdoor environments.
- **Simple** - Direct line voltage (100 to 240 VAC) input eliminates the need for remote power supply unit, minimizing the system components and risk points, allowing for an easy and fast installation.



[Product page](#)

Beam Angles	10°, 20°, 40°
Lumens*	2,395 to 2,603
Efficacy	33.8 to 37
LED Channels	Red/Green/Blue
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

Input Voltage	100 to 240 VAC, 50/60 Hz
Power Consumption	44 W
Weight	3.53 kg (7.8 lb)
Housing Material	Die-cast aluminium, dark grey powder-coated finish
Approbations	PSE, CQC, RCM, BIS
Environment	Dry/Damp/Wet Location, IP66

Specification Sheets

PDF Download	Beam Angle	Lumens*	Item Number	12 NC
RGB, 10°, CE/CQC/PSE	10°	2,603	316-000016-00	912400133977
RGB, 20°, CE/CQC/PSE	20°	2,567	316-000016-01	912400133978
RGB, 40°, CE/CQC/PSE	40°	2,395	316-000016-02	912400133979
RGB, 10°, UL	10°	2,603	316-000016-04	912400133980
RGB, 20°, UL	20°	2,567	316-000016-05	912400133981
RGB, 40°, UL	40°	2,395	316-000016-06	912400133982
RGB, 10°, BIS	10°	2,603	316-000016-07	912400137261
RGB, 20°, BIS	20°	2,567	316-000016-08	912400137262
RGB, 40°, BIS	40°	2,395	316-000016-09	912400137263

* Lumen output measurements comply with IES LM-79-08 testing procedures.

© 2021 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

www.colorkinetics.com/global/products/vaya/flood-mp-g2-rgb

21 October 2021

COLOR KINETICS vaya series