



Date: _____
Type: _____
Firm Name: _____
Project: _____

SkyRibbon IntelliHue Wall Washing

Recessed linear interior LED wall washing luminaire with intelligent white and color light



[Product page](#)

Introducing SkyRibbon IntelliHue Wall Washing Powercore, a recessed linear interior LED wall washing luminaire offering high-quality intelligent color and white light from the same luminaire. IntelliHue is an advanced approach to color mixing that gives users the ability to precisely target a full spectrum of saturated color and high-quality white light, granting an unprecedented level of design freedom. Brilliant light output and industry-leading controls make luminaires ideal for a variety of interior wall washing applications. Users can rotate LED modules from 0° to 90° to evenly wash walls top to bottom regardless of luminaire setback. Multiple housing options accommodate a number of installation methods.

- Color-changing and high-quality white light from the same luminaire—IntelliHue is an advanced approach to color mixing that enables high-quality intelligent color and white light from a single luminaire. Multiple channels of LED light sources combine to produce a full spectrum of precisely controllable light, including millions of saturated colors, pastels, and uniform white light with CRI of greater than 85 in the 2700 K – 4000 K range.

Beam Angle	20° x 20°, 30° x 30°, 30° x 60°, 35° x 105°, 40° x 80°, 65° x 65°, 70° x 95°, 90° x 90°
Lumens @ 4000 K*	1,813 to 2,867
LED Channels ^s	Red/Green/Blue/Mint White/4000 K
Input Voltage	120 VAC/220 to 240 VAC/277 VAC, 50/60 Hz
Weight	4.7 kg (10.4 lb)
Housing Material	Steel
Approbations	UL/cUL, FCC Class A, CE
Environment	Dry/Damp Location, IP20
Applications	Wall Washing

20° x 20° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 20° x 20° Beam Angle	20° x 20°	2,867	33.4	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 20° x 20° Beam Angle	20° x 20°	2,867	33.4	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 20° x 20° Beam Angle	20° x 20°	2,867	33.4	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

30° x 30° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 30° x 30° Spread Lens	30° x 30°	2,479	28.6	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 30° x 30° Spread Lens	30° x 30°	2,479	28.6	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 30° x 30° Spread Lens	30° x 30°	2,479	28.6	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

30° x 60° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 30° x 60° Spread Lens	30° x 60°	2,376	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 30° x 60° Spread Lens	30° x 60°	2,376	27.9	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 30° x 60° Spread Lens	30° x 60°	2,376	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

35° x 105° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 35° x 105° Spread Lens	35° x 105°	2,418	28.2	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 35° x 105° Spread Lens	35° x 105°	2,418	28.2	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 35° x 105° Spread Lens	35° x 105°	2,418	28.2	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

40° x 80° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 40° x 80° Spread Lens	40° x 80°	2,378	28	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 40° x 80° Spread Lens	40° x 80°	2,378	28	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 40° x 80° Spread Lens	40° x 80°	2,378	28	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

65° x 65° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 65° x 65° Spread Lens	65° x 65°	2,395	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 65° x 65° Spread Lens	65° x 65°	2,395	27.9	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 65° x 65° Spread Lens	65° x 65°	2,395	27.9	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

70° x 95° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 70° x 95° Spread Lens	70° x 95°	2,330	27.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 70° x 95° Spread Lens	70° x 95°	2,330	27.1	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 70° x 95° Spread Lens	70° x 95°	2,330	27.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

90° x 90° Specification Sheets

PDF Download	Beam Angle	Lumens @ 4000 K*	Efficacy	Power	Weight	Item Number	12 NC
120 VAC, 90° x 90° Spread Lens	90° x 90°	1,813	21.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668
220 – 240 VAC, 90° x 90° Spread Lens	90° x 90°	1,813	21.1	66 W	4.7 kg (10.4 lb)	123-000072-01	910503704253
277 VAC, 90° x 90° Spread Lens	90° x 90°	1,813	21.1	66 W	4.7 kg (10.4 lb)	123-000072-00	910503702668

* Lumen output measurements comply with IES LM-79-08 testing procedures.

§ Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.