

eW Reach Compact Powercore

Premium long-throw exterior LED floodlight with solid white light

Date: _____
Type: _____
Firm Name: _____
Project: _____

eW Reach Compact Powercore high-performance LED luminaires are premium exterior long-throw dynamic high-quality white luminaires for lighting tall buildings, bridges, and iconic structures. eW Reach Compact Powercore outputs washes of white light in color temperatures ranging from a warm 2700 K to a cool 4000 K. A full range of accessories allow for customizable beam angles for floodlighting, spotlighting, wall washing, and grazing, along with the efficiency and cost-effectiveness of Powercore technology in a rugged die-cast aluminium housing.

- Multiple options for design flexibility—Luminaires are available in a warm 2700 K or a cool 4000 K. Custom configurations with custom channels of white or color LED sources are also available to support special applications.
- Superior color consistency and accuracy—Optibin, an advanced binning algorithm, sets a new standard for the color consistency and uniformity of LED sources used in manufacturing resulting in color consistency within 2 SDCM.
- Digital Dimming—Smooth dimming down to 1% with optional Data Enabler Pro and digital control interface.



[Product page](#)

Beam Angle	5°, 8°, 13°, 23°, 43°, 63°, 5° x 17°
Lumens*	5,736 to 7,441
Color Temperature [§]	2700 K, 4000 K

Input Voltage	100 to 240 VAC, auto-ranging, 50/60 Hz (CQC) 100 to 277 VAC, auto-ranging, 50/60 Hz (UL/CE)
Power Consumption	125 W
Weight	23.4 kg (51.6 lb)
Housing Material	Die-cast aluminium, powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, C-Tick
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

2700 K Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
2700 K, 5° Native (no spread lens), CQC	5°	6,562	55.8	523-000084-26	912400133502		
2700 K, 5° Native (no spread lens), UL/CE	5°	6,562	55.8	523-000095-12	912400133469		
2700 K, 8° Spread Lens, CQC	8°	6,053	49.5	523-000084-26	912400133502	120-000068-17	912400133598
2700 K, 8° Spread Lens, UL/CE	8°	6,053	49.5	523-000095-12	912400133469	120-000068-17	912400133598
2700 K, 13° Spread Lens, CQC	13°	6,047	49.4	523-000084-26	912400133502	120-000068-12	912400133593
2700 K, 13° Spread Lens, UL/CE	13°	6,047	49.4	523-000095-12	912400133469	120-000068-12	912400133593
2700 K, 23° Spread Lens, CQC	23°	5,901	48.2	523-000084-26	912400133502	120-000068-13	912400133594
2700 K, 23° Spread Lens, UL/CE	23°	5,901	48.2	523-000095-12	912400133469	120-000068-13	912400133594

2700 K Specification Sheets (cont.)

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
2700 K, 43° Spread Lens, CQC	43°	5,766	47.1	523-000084-26	912400133502	120-000068-14	912400133595
2700 K, 43° Spread Lens, UL/CE	43°	5,766	47.1	523-000095-12	912400133469	120-000068-14	912400133595
2700 K, 63° Spread Lens, CQC	63°	5,736	46.9	523-000084-26	912400133502	120-000068-15	912400133596
2700 K, 63° Spread Lens, UL/CE	63°	5,736	46.9	523-000095-12	912400133469	120-000068-15	912400133596
2700 K, 5° x 17° Asymmetric Spread Lens, CQC	5° x 17°	6,065	48.1	523-000084-26	912400133502	120-000068-16	912400133597
2700 K, 5° x 17° Asymmetric Spread Lens, UL/CE	5° x 17°	6,065	48.1	523-000095-12	912400133469	120-000068-16	912400133597

4000 K Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
4000 K, 5° Native (no spread lens), CQC	5°	7,441	59.8	523-000084-29		912400133505	
4000 K, 5° Native (no spread lens), UL/CE	5°	7,441	59.8	523-000095-18		912400133475	
4000 K, 8° Spread Lens, CQC	8°	6,729	53.3	523-000084-29	120-000068-17	912400133505	912400133598
4000 K, 8° Spread Lens, UL/CE	8°	6,729	53.3	523-000095-18	120-000068-17	912400133475	912400133598
4000 K, 13° Spread Lens, CQC	13°	6,680	52.9	523-000084-29	120-000068-12	912400133505	912400133593
4000 K, 13° Spread Lens, UL/CE	13°	6,680	52.9	523-000095-18	120-000068-12	912400133475	912400133593
4000 K, 23° Spread Lens, CQC	23°	6,446	51.1	523-000084-29	120-000068-13	912400133505	912400133594
4000 K, 23° Spread Lens, UL/CE	23°	6,446	51.1	523-000095-18	120-000068-13	912400133475	912400133594
4000 K, 43° Spread Lens, CQC	43°	6,500	51.5	523-000084-29	120-000068-14	912400133505	912400133595
4000 K, 43° Spread Lens, UL/CE	43°	6,500	51.5	523-000095-18	120-000068-14	912400133475	912400133595
4000 K, 63° Spread Lens, CQC	63°	6,449	51.1	523-000084-29	120-000068-15	912400133505	912400133596
4000 K, 63° Spread Lens, UL/CE	63°	6,449	51.1	523-000095-18	120-000068-15	912400133475	912400133596
4000 K, 5° x 17° Asymmetric Spread Lens, CQC	5° x 17°	6,065	48.1	523-000084-29	120-000068-16	912400133505	912400133597
4000 K, 5° x 17° Asymmetric Spread Lens, UL/CE	5° x 17°	6,065	48.1	523-000095-18	120-000068-16	912400133475	912400133597

* Lumen output measurements comply with IES LM-79-08 testing procedures.

† Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.



© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/ls/essentialwhite/ewreachcompact/