

EvenBalance Essential White Powercore

Date: _____
Type: _____
Firm Name: _____
Project: _____

3000 K, 305 mm (1 ft), Washing

Interior linear OptiField luminaire with single temperature white light

EvenBalance Essential White Powercore is a compact interior linear luminaire that is ideal for washing and grazing applications. OptiField delivers extremely uniform illuminance, providing smooth, even light and subtle shading with reduced setbacks—without hotspots or banding. Two beam spreads: Washing and Grazing, two lengths: 305 mm (1 ft) and 1219 mm (4 ft), and the ability to continuously rotate the luminaire up to 180° enable a high degree of flexibility.



- Uniform illumination—EvenBalance Essential White Powercore delivers a uniformity ratio of less than 3:1 on a 3 m (9 ft) wall with an 0.5 m (1.5 ft) setback.
- Precise control of light—Asymmetric optic design provides precise control of light and delivers more illumination with higher uniformity at a lower power than comparable fluorescent asymmetric reflector solutions.
- Grazing and Washing options—The grazing beam spread of EvenBalance eW Powercore evenly accentuates the surface of a textured wall at a 50 mm (2 in) setback. The washing beam spread is designed to evenly illuminate flat surfaces, such as drywall, with a high illuminance, using a 150 mm to 500 mm (0.5 to 1.5 ft) setback.
- Integrates patented Powercore technology—Powercore rapidly, efficiently, and accurately controls power directly from line voltage, eliminating the need for an external power supply. Contractor-friendly installation dramatically simplifies installation and lowers total system cost.
- Multiple color temperatures—Available in 2700 K, 3000 K, 3500 K, and 4000 K color temperatures for applications calling for warm, neutral, or cool white light.
- Simple installation—The linear design and small form factor of EvenBalance Essential White Powercore makes it easy to install, conceal, in tight interior spaces. The 180° continuous rotation and constant torque rotation make the luminaire extremely adaptable in any application.
- Support for multiple voltages—Accepts line voltage of 100 to 277 VAC for consistent installation and operation around the world.
- Smooth dimming capability—Smooth dimming capability—Patented DIMand technology offers smooth dimming capability with the DM-1000 0-10 V ELV Dimmer or selected reverse-phase ELV-type dimmers.

For detailed product information, please refer to the EvenBalance Product Guide at www.colorkinetics.com/global/products/essentialwhite/evenbalance/

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Output

| | |
|--------------------|---|
| Color Temperature* | 3000 K |
| Beam | Washing with 150 to 500 mm (6 to 18 in) setback |
| Lumens† | 927 |
| Efficacy (lm/W) | 79.1 |
| CRI | 81 |

Electrical

| | |
|---|--|
| Input Voltage | 100 to 277 VAC, auto-ranging, 50/60 Hz |
| Power Consumption (Maximum at full output, steady state) | 12.5 W |
| Power Factor | 0.99 @ 120 VAC |
| Surge Limits‡ | 0.5 kV maximum differential (L to N) 1 kV maximum common (L to Gnd or N to Gnd) |

For additional Surge Protection Requirements for LED Lighting Systems, please refer to www.colorkinetics.com/KB/surge-protection.

Control

Dimmer

Compatible with selected commercially available reverse-phase ELV-type dimmers

Lumen Maintenance

| Threshold§ | Ambient Temperature | Reported¶¶ | Calculated¶¶ |
|-----------------|---------------------|------------|--------------|
| L ₉₀ | 25 °C | > 54,000 | |
| | 50 °C | > 54,000 | |
| L ₈₀ | 25 °C | | > 100,000 |
| | 50 °C | | > 100,000 |
| L ₇₀ | 25 °C | | > 100,000 |
| | 50 °C | | > 100,000 |

* Correlated color temperature (CCT) complies with ANSI C78.377-2008 for the chromaticity of solid state lighting products.

† 305 mm (1 ft) lumen output measurements comply with IES LM-79-08 testing procedures. 1219 mm (4 ft) measurements are estimated based on the 305 mm (1 ft) measurements.

‡ Refer to www.colorkinetics.com/support/appnotes/ for more information.

§ L_{xx} = 70% lumen maintenance (when light output drops below 70% of initial output). All values are given at B10, or the median value where 90% of the LED population is better than the reported or calculated lumen maintenance measurement.

¶ Minimum surge limits per IEC 61547, tested in accordance with IEC 61000-4-5.

¶¶ Lumen maintenance figures are based on lifetime prediction graphs supplied by LED source manufacturers. Whenever possible, figures use measurements that comply with IES LM-80-08 testing procedures. In accordance with TM-21-11, Reported values represent the interpolated value based on six times the LM-80-08 total test duration (in hours). Calculated values represent time durations that exceed six times the total test duration.

Physical

| | |
|--|--|
| Dimensions (Height x Width x Depth) | 54 x 305 x 39 mm (2.1 x 12 x 1.5 in) |
| Weight | 445 g (0.98 lb) |
| Housing Material | Die-cast aluminium, white powder-coated finish |
| Lens | Polycarbonate |
| Luminaire Connections | Integral male/female connectors |

Temperature Ranges

| |
|--|
| -40 to 50 °C (-40 to 122 °F) Operating |
| -20 to 50 °C (-4 to 122 °F) Startup |
| -40 to 80 °C (-40 to 176 °F) Storage |

| | |
|----------|--------------------------|
| Humidity | 0 to 95%, non-condensing |
|----------|--------------------------|

Luminaire Run Lengths

To calculate luminaire run lengths and total power consumption for your specific installation, download the Configuration Calculator from www.colorkinetics.com/support/install_tool/

Certification and Safety

| | |
|-------------|----------------------------------|
| Approbation | UL/cUL, FCC Class B, C-Tick, CCC |
| Environment | Dry/Damp Location, IP20 |



Luminaire and Accessories

Use Item Number when ordering in North America

| Luminaire | Item Number | Item 12NC |
|--|--------------------|------------------|
| EvenBalance Essential White Powercore, 3000 K, 305 mm (1 ft), Washing | 523-000099-09 | 912400134220 |
| Accessories | | |
| Leader Cable with Terminator and Strain Relief, UL/cUL, 3 m (10 ft) | 108-000047-00 | 910503700972 |
| Leader Cable with Terminator and Strain Relief, CE/CCC, 3 m (10 ft) | 108-000047-01 | 910503700973 |
| Wiring Compartment with Terminator, UL/cUL, 44.5 x 44.5 x 111.1 mm (1.75 x 1.75 x 4.38 in) | 120-000077-01 | 910503700994 |
| Jumper Cable, UL/cUL, 305 mm (12 in) | 108-000048-00 | 910503700974 |
| Jumper Cable, UL/cUL, 1.5 m (5 ft) | 108-000048-01 | 910503700975 |
| Jumper Cable, CE/CCC, 305 mm (12 in) | 108-000048-02 | 910503700976 |
| Jumper Cable, CE/CCC, 1.5 m (5 ft) | 108-000048-03 | 910503700977 |
| Terminators, Box of 10 | 120-000099-00 | 910503701120 |
| Mounting Track, White, 1219 mm (4 ft) | 120-000124-00 | 910503701787 |
| DM-1000 0-10 V ELV Dimmer | 109-000036-00 | 912400135916 |



© 2021 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/global/products/essentialwhite/evenbalance/