4 Conductor Jumper Cable

Date:			
Type:			
Firm Name:			
Project:			

For use with Graze MX/QLX/EC luminaires, 3 m (10 ft), Black, UL/cUL

JUMPER CABLE

For use with Graze MX/QLX/EC Powercore luminaires



Specifications

Due to continuous improvements and innovations, specifications may change without notice.


Physical

Dimensions		3048 mm (120 in) _{Length}	
Weight		0.77 kg (1.69 lb)	
Connections		Self-locking, male-female connectors	
Cable	4 conductor, Ann	nealed flexible stranded copper, EN 50525-2- 21	
Outer Ca	able Insulation	EM2 60° C, not halogen free	
Inner Wire Insulation		EPR (Ethylene Propylene Rubber)	
Wire Ga	uge	14 AWG	
Voltage		100 to 277 VAC	
Temperature Range		-40 to 50 °C (-40 to 122 °F) Operating	

Certification and Safety

Environment	Dry/Damp/Wet Location, IP66
Certification	UL/cUL

Dimensions



Ø 10.03 mm (0.4 in)

Part Numbers

Use Item Number when ordering in North America.

Ø 20.8 mm (0.82 in)

Jumper CableItem NumberItem 12NC4 Conductor Jumper Cable108-000057-09910503704082For use with Graze MX/QLX/EC luminaires, 3 m (10 ft), Black, UL/cULAllows end-to-end connection of units with 10 ft gapZCS459 C3050P-M-F BK UL

 \odot 2021 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.



