



Date: _____ Type: _____

Firm Name: _____

Project: _____

iColor Flex MX

Flexible strands of high-intensity LED nodes with intelligent color light

Ordering Information

Select one component from each column to specify a complete configuration.

Node Count	Node Spacing	Node / Cable Color	Lens
5	2 in	White	Clear Dome
•	3 in	Black	Clear Flat
•	4 in	Clear	Translucent Flat
50	•		Translucent Dome
•	•		
•	12 in		
72	•		
	•		
	24 in		

In addition to the standard node count of 50 per string, you can specify any node count between 5 and 72 per string.

In addition to standard node spacing of 4 in and 12 in on center, you can specify any on-center node spacing from 2 in to 24 in, in English or metric units.

= Standard component

Standard Configurations

If you select all standard components (shaded red), find your configuration in the standard configurations list, and order using the Item Number or Philips 12NC. Standard configurations are not subject to minimum order quantities or extended production lead times.

Standard Configuration Example:

iColor Flex MX, 50 nodes, 12 in, White node / cable, Clear Dome lens

(Use Item Number 101-000068-05 or Philips 12NC 910503700713)

Custom Configurations

If you select one or more non-standard (non-shaded) components, your configuration is custom.

Minimum Order Quantity: 10 strings per configuration

Production Lead time: 12 weeks ARO (standard shipping options apply)

Custom Configuration Example:

Special, iColor Flex MX, 25 nodes, 100 mm, Clear node / cable, Translucent Dome lens

(Contact your Philips Color Kinetics Lighting Sales group with the product description for custom configurations.)

In North America contact: Philips Color Kinetics Sales, 888.385.5742 or sales@colorkinetics.com



iColor Flex MX Standard Configurations

Item	Type		Item Number	Philips 12NC
iColor Flex MX 50 nodes 4 in on-center node spacing	White	Clear Dome Lens	101-000068-04	910503700712
		Translucent Dome Lens	101-000068-00	910503700708
	Black	Clear Dome Lens	101-000068-06	910503700714
		Translucent Dome Lens	101-000068-02	910503700710
iColor Flex MX 50 nodes 12 in on-center node spacing	White	Clear Dome Lens	101-000068-05	910503700713
		Translucent Dome Lens	101-000068-01	910503700709
	Black	Clear Dome Lens	101-000068-07	910503700715
		Translucent Dome Lens	101-000068-03	910503700711
Leader Cables	Black	25 ft (7.6 m)	108-000045-00	910503700696
		50 ft (15.2 m)	108-000045-01	910503700697
		100 ft (30.5 m)	108-000045-02	910503700698
Mounting Track Qty 1	White	4 ft (1.2 m)	101-000024-00	910503700015
	Black		101-000024-01	910503700016
Mounting Track Spacers Qty 50	White	4 in (102 mm)	101-000047-00	910503700030
	Black		101-000047-01	910503700031
	White	12 in (305 mm)	101-000048-00	910503700032
	Black		101-000048-01	910503700033
Single Node Mounts Qty 50	White		101-000039-00	910503700025
	Black		101-000039-01	910503700026
PDS-60ca 7.5V	Pre-programmed		109-000015-00	910503700093
	DMX / Ethernet		109-000015-03	910503700094
sPDS-480ca 7.5V	Ethernet		109-000022-00	910503700107

Use Item Number when ordering in North America.



CHROMACORE CK TECHNOLOGY | CHROMASIC CK TECHNOLOGY | OPTIBIN CK TECHNOLOGY

Features

iColor Flex MX is a flexible strand of high-intensity, full-color LED nodes designed for extraordinary effects and expansive installations without the constraints of fixture size or shape. Each iColor Flex MX strand consists of a series of individually addressable LED nodes, featuring dynamic integration of power, communication, and control. iColor Flex MX enables patterns and video on almost any interior or exterior surface, including ceilings, floors, three-dimensional objects, sculptures, and more. Its small node size allows installation in tighter spaces than the larger iColor Flex SLX and iColor Flex LMX strands.

Custom configurations allow you to specify any node count from 5 to 72 per strand, any on-center node spacing between 2 in and 24 in, and additional node / cable colors and lens options.

- Superior light output of up to 1.44 candela per node (full on)
- Multiple lens options, including standard clear and translucent dome lenses, and optional clear and translucent flat lenses
- Mount strings directly to a surface, use optional mounting track for straight linear runs, or use optional single node mounts for installations with uneven spacing.
- Fully sealed for maximum fixture life and IP66-rated for outdoor applications.

For detailed product information, please refer to the iColor Flex MX Product Guide at www.philipscolorkinetics.com/ls/rgb/flexmx/



Philips Color Kinetics
3 Burlington Woods Drive
Burlington, Massachusetts 01803 USA
Tel 888.385.5742
Tel 617.423.9999
Fax 617.423.9998
www.philipscolorkinetics.com

Copyright © 2009 – 2012 Philips Solid-State Lighting Solutions, Inc. All rights reserved.
Chromacore, Chromasic, CK, the CK logo, Color Kinetics, the Color Kinetics logo, ColorBlast, ColorBlaze, ColorBurst, eW Fuse, ColorGraze, ColorPlay, ColorReach, iW Reach, eW Reach, DIMand, EssentialWhite, eW, iColor, iColor Cove, IntelliWhite, iW, iPlayer, Optibin, and Powercore are either registered trademarks or trademarks of Philips Solid-State Lighting Solutions, Inc. in the United States and / or other countries. All other brand or product names are trademarks or registered trademarks of their respective owners. Due to continuous improvements and innovations, specifications may change without notice. DAS-000049-02 R04 07-12